

FLOOR GRINDERS

The ABPG 270 is an excellent light-weight Machine for concrete cleaning and grinding, quick and easy removal of coatings and adhesives. The ideal equipment to deliver the best possible Surface Preparation before the application of a new coating. The Machine is designed for contractors who need a light-weight machine for small and medium sized jobs.

- Working width 270 mm with 4 diamond tools
- For instant change of diamond tools on job site: "Easy-Click"
- The Tool Holder is designed to fit with magnetic adapters 4 diamond tools
- Removable side plate for edge cleaning work
- The Axel height is easily adjusted for the operators ease of use
- Steel body construction
- Excellent dust control with the effective shroud with vacuum port will keep the working environment clean and away from abrasive dust particles



BPG 450 „TRIO-TEC“ Floor Grinder-Polisher with 3 Counter Rotating Tool Heads. Compact robust steel design. Ideally suited to prepare and polish surfaces.

- The 3-Counter-Rotating heads add stability and produce a superior finish.
- Easy coupling to industrial Dust Collection System
- Dust Control Protects against silica and other dusts
- The handle can be adjusted to a height that suits the operator
- Removable side plate to work up to the edge of the wall
- For dry and wet applications
- "Easy Click" quick Tool Change System
- Soft on Floors tough on coatings
- Steel Body construction



The BPG 520 is extremely aggressive, but floor friendly in removal of all types of thick coatings, underlayments and high spots in floors.

- Clamping lever
- Dust shroud with rubber seal
- Rubber wheels 50 x 160 mm
- Connection for Industrial extractor
- Emergency stop switch
- Special screw for transport
- Security switch



TECHNICAL DATA	BPG270
Motor	2.2 kW (Electric)
Weight	57 kg
Tool Plate Rotation	1500 rpm (constant Rotation) 300 – 2000 rpm (Model SPC)
Working Width	270 mm

TECHNICAL DATA	BPG450
Motor	2.2 kW (Electric)
Voltage	230 V and 400 V
Motor speed	1460 rpm (constant Rotation)
Working Width	450 mm

TECHNICAL DATA	BPG520
Motor	3 kW (Electric)
Voltage	400 V / 50/60 Hz, 6.4 A
Motor speed	1450 rpm
Working Width	520 mm