



PROFESSIONAL HEAVY DUTY CEMENT MIXER

BP 400 4R



TECHNICAL SPECIFICATIONS

Max. Drum Capacity (Tolerance +/- 10%) (Ltrs.)	360
Max. Mixing Capacity (Tolerance +/- 10%) (Ltrs.)	315
Dosage (Kgs)	2 x 35
Drum Rotation Speed (rpm)	25
Production Per Hour (m³)	3.20
No. of Double Mixing Blades (Nos.)	3
Weight Without Engine (Kgs)	240
Engine Type	Electric - Petrol - Diesel
Reinforced Structure	Yes
Finishing	Epoxy Paint
Dimensions (L x W x H) mm	1810 x 1100 x 1650


ELECTRIC MOTOR		SINGLE-PHASE		THREE-PHASE			
Voltage (V)		220 / 240		380 / 400			
Flow (A)		4.20		1.38			
Power (Kw)		0.55		0.55			
Frequency (Hz)		50		50			
ENGINE	SUBARU	HONDA		KIPOR		LOMBARDINI	HATZ
Model	SP170	GX120	GX160	GK178	KM178F	15 LD 225	1B20
Fuel	Petrol				Diesel		
Displacement (cm³)	169	118	163	168.3	296	224	232
Power (Kw/Hp)	2.90	2.60 / 3.50	3.60 / 4.80	3.30 / 4.43	3.68 / 4.90	3.50 / 4.80	2.80 / 3.75
Weight (Kgs)	15	13	15.1	25	33	28	



Drum with Reinforced
Opening and 3
Double Mixing Blades



Lubrication Point



Cast Iron Gear Ring



Reinforced Structure



Flexible Axis



Poly - V Cast Iron
and Trapezoidal Belt

